

GOETZE Spring-loaded safety valve Type 2379 stainless steel dairy coupling DIN11851

Characteristics

Type: 2379

Model: Spring-loaded

Construction type: Angle Pattern

Housing material inlet side: Stainless steel

Material quality inlet side: 1.4435

Housing material outlet side: Stainless steel

Material quality outlet side: 1.4435 Connection inlet side: Food coupling Standard connection inlet side: DIN 32676 Connection outlet side: Food coupling Standard connection outlet side: DIN 32676

Material spring bonnet: 1.4404

Spring material: 1.4310

Medium temperature: -40 / 200 °C

Application

• Recommended in: Food & Beverages

Nominal inner diameter inlet side	Nominal inner diameter outlet side	Adjustment range	Valve bore	Sealing	Article
		bar	mm		
DN20	DN25	0.4 / 16	18	FPM	12734868
DN25	DN25	0.4 / 16	18	FPM	12734869

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be



Page 1/1

PR1440397336609_EN_19.05.2024