



GF 3-way coupling in PVC-U Serie: 510 Glued sleeve

Characteristics

- Series:** 510
- Material:** PVC-U
- Connection:** Glued sleeve
- Seal material:** FPM (FKM)
- Minimum medium temperature (continuous):** 0 °C
- Maximum medium temperature (continuous):** 60 °C

Shape	External tube diameter of connection mm	Pressure rating	Article
3-piece coupling	10	PN16	10045711
3-piece coupling	12	PN16	10045712
3-piece coupling	16	PN16	10045713
3-piece coupling	20	PN16	10045714
3-piece coupling	20	PN16	11235099
3-piece coupling	25	PN16	11195676
3-piece coupling	25	PN16	10045715
3-piece coupling	32	PN16	10045716
3-piece coupling	40	PN16	10045717
3-piece coupling	50	PN16	10045718
3-piece coupling	63	PN16	10045719
3-piece coupling	75	PN16	10045720
3-piece coupling	75	PN16	11104460
3-piece coupling	110	PN16	10045722

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.