




ECON® Diaphragm drum pressure gauge Type 1481C back connection brass front flange

Characteristics

Type: 1481C
Accuracy class: 1.6 %
Pressure gauge attachment: Wall flange
Connection location: Back
Process connection: External thread
Cabinet material: Stainless steel 304

Characteristics [2]

Process connection material: Brass
Material dial: Aluminium
Protection class: IP54
Medium temperature: -20 / 60 °C
Ambient temperature: -20 / 60 °C



Cabinet diameter	D	b	c	c1	c2	c3	d1	d2	d3	G	G1	g	g1	SW	s2	s3	Weight
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
63	64	47	5	2	13	13	75	85	3.7	85	3.7	59	59	14	2	5	0.23
100	101	55	6	3	20	19	116	132	4.8	132	4.8	85	84	22	2	6	0.5
160	161	51.5	6	3	20	19	178	196	5.8	196	5.8	82	81	22	2	6	0.9

Cabinet diameter mm	Measuring range	Pressure unit	Size process connection	Window material	Article
63	-400 / 0	mbar	1/4" BSPP[G]	Acrylic	11233981
63	-250 / 0	mbar	1/4" BSPP[G]	Acrylic	11322884
63	0 / 100	mbar	1/4" BSPP[G]	Acrylic	12186729
63	0 / 160	mbar	1/4" BSPP[G]	Acrylic	11341827
63	0 / 250	mbar	1/4" BSPP[G]	Acrylic	11346354

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.