

GOODALL Rubber Hose Inferno steam hose with 2 x single flange coupling in steel PN40

Rubber steam hose Inferno, for high pressure saturated steam to 232 °C. With specially designed on both sides DuraCrimp steam couplings, pressed-on. This assembly provides a 100% leak-proof seal. And additional handle can also be fitted.

Benefits of the Inferno hose

gas-tight inner wall which prevents popcorning

Higher temperature resistance

Double reinforcement plies for higher burst pressures.

Specially processed steel wires and insert that are less susceptible to corrosion.

Clear red spiral mark

Bare headed hose, can be used in all ATEX zones.

Benefits DuraCrimpcoupling system

100% secure and leak-free assembly Lighter than clamps No problems with loosening of bolts (as with clamps) Mounting is performed by Eriks skilled people.

Benefits red handle

Prevents kinking behind the coupling Ergonomic handle Better thermal insulation (protective clothing is always required) Color coding possible means of identification rings Ability to bring easy to a RFID chip.

Characteristics

Series: Inferno

Internal diameter	Wall thickness	Maximum operating pressure	Roll length	Article
mm	mm	bar	m	
13	6	18	15	12753801
19	7	18	15	12753822
25	7.5	18	15	12753843

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR1444037409552_EN_15.05.2024