



Flange coupling with knurled tailpiece, type SHLF/SHFF

Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Flange

Hose fitting type: Fixed flange

Connection termination: EN1092 PN40

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
DN50	DN50	16	232	10069905
DN65	DN63	16	232	10069906
DN80	DN75	16	232	10069907
DN100	DN100	16	232	10070089
DN150	DN150	16	232	10070090
DN25	DN25	40	580	10069902
DN32	DN32	40	580	10069903
DN40	DN38	40	580	10069904
DN200	DN200	10	145	10070091
DN250	DN250	10	145	10070092
DN50	DN50	16	232	10037964
DN65	DN65	16	232	13530648
DN80	DN75	16	232	10037991
DN100	DN100	16	232	10037992
DN125	DN125	16	232	10037978
DN150	DN150	16	232	10037966
DN25	DN25	40	580	10037990
DN32	DN32	40	580	10037974
DN40	DN40	40	580	10037963
DN50	DN50	40	580	13543322

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.