



HONEYWELL Pressure reducing valve Type 11201 series D22A brass internal thread

Characteristics

Series: D22A

Type: 11201

Model: Direct-acting

Connection: Internal thread [BSPP]

Maximum inlet pressure: 40 bar

Medium temperature: 0 / 70 °C

Suitable for gases: 0

Housing material: Brass

Membrane material: NBR

Spring material: Spring steel

Material spring bonnet: Synthetic material

Backflow preventer: No

DN ["]	L mm	H mm	h mm	Weight [kg]	Kvs-value [m ³ /h]
1/4	50	90	34	0,3	0,9
3/8	50	90	34	0,3	1
1/2	65	105	36	0,45	1,5
3/4	80	105	42	0,6	2,5
1	95	150	57	1,35	5
1 1/4	105	160	57	1,8	6
1 1/2	115	200	72	2,9	11,5
2	130	210	72	3,8	12,5

Min./Max.	Press./Temp.
Max.oper. press.	40bar
Max. temperature	70°C
Min. press. difference	1 bar

Nominal inner diameter	Capacity type	Reduced pressure range bar	Article
1.1/4" [32]	Standard	1 / 10	10051493
1.1/2" [40]	Standard	1 / 10	10051492
2" [50]	Standard	1 / 10	10051487

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.