



Flange coupling with knurled tailpiece, type SHLF - steel - EN1092-1

Characteristics

Type of component: Hose tail coupling

Material: Tail AISI316/ Flange Steel

Connection type: Flange

Hose fitting type: Swivel Flange

Connection termination: EN1092 PN40

Elbow angle [degr.]: 0 °

Hose tail execution: Smooth, with safety collar

Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
DN50	DN50	16	232	10069892
DN65	DN63	16	232	10069894
DN80	DN75	16	232	10069897
DN100	DN100	16	232	10070094
DN150	DN150	16	232	10070096
DN15	DN12	40	580	11271898
DN25	DN25	40	580	10037979
DN32	DN32	40	580	10069887
DN40	DN38	40	580	10069890
DN50	DN50	40	580	12493635
DN80	DN75	40	580	12493645
DN100	DN100	40	580	12493636
DN20	DN19	40	580	11271899
DN50	DN50	16	232	10069893
DN65	DN63	16	232	10069895
DN80	DN75	16	232	10069898
DN100	DN100	16	232	10070093
DN150	DN150	16	232	10070095
DN15	DN12	40	580	12493639
DN20	DN19	40	580	12493632
DN25	DN25	40	580	12493634
DN32	DN32	40	580	10069888
DN40	DN38	40	580	10069891
DN80	DN75	40	580	12493644

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.