



Flange coupling with knurled tailpiece, type SHLF - ANSI

Characteristics

- Type of component: Hose tail coupling
- Material: Tail AISI316/ Flange Steel
- Connection type: Flange
- Hose fitting type: Swivel Flange
- Connection termination: EN1092 PN16
- Elbow angle [degr.]: 0 °
- Hose tail execution: Serrated, with safety collar
- Temperature range [°C]: -40 / 100 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/2"	DN12	18.9	274	12493640
3/4"	DN19	18.9	274	12493641
1"	DN25	18.9	274	11476745
1.1/4"	DN32	18.9	274	12493643
1.1/2"	DN38	18.9	274	11624872
2"	DN50	18.9	274	11092089
2.1/2"	DN63	18.9	274	12493627
3"	DN75	18.9	274	11474379
4"	DN100	18.9	274	11476746
5"	DN125	18.9	274	12493629
2"	DN50	49.6	719	11400853
4"	DN100	49.6	719	12493646
DN200	DN200	16	232	13580391
3/4"	DN19	19.6	284	12493642

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.