



CENTER LINE RS Butterfly valve Type: 713 Ductile cast iron/ Stainless steel Pneumatic operated Double acting Wafer type



Characteristics

Type: 713

Norm: EN (DIN)

Valve design: Centric

Housing material: Ductile cast iron

Material quality: EN-JS1030

Surface protection: Epoxy

Connection: Wafer type

Standard connection: EN (DIN)

Face to Face norm: EN 558, Series 20

Operation: Pneumatic operated

Characteristics [2]

Operating principle: Double acting

Brand actuator: AMG


Top flange standard: ISO 5211 Direct Mount

Housing lining: Replaceable

Disk material: Stainless steel

Quality class disc: 1.4408

Actuator material: Aluminium



Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Type coding actuator	Material liner	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
			mm			°C	°C	
DN50	PN10	PN10	43	SAD10	EPDM	-10	120	10056638
DN65	PN10	PN10	46	SAD10	EPDM	-10	120	10056639
DN80	PN10	PN10	46	SAD15	EPDM	-10	120	10056640
DN100	PN10	PN10	52	SAD15	EPDM	-10	120	10056641
DN125	PN10	PN10	56	SAD20	EPDM	-10	120	10056642
DN150	PN10	PN10	56	SAD25	EPDM	-10	120	10056643
DN200	PN10	PN10	60	SAD25	EPDM	-10	120	10056644
DN250	PN10	PN10	68	SAD30	EPDM	-10	120	10056645
DN300	PN10	PN10	78	SAD33	EPDM	-10	120	10056646

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.