


GOODALL Rubber hose Nutralon, NBR foodstuff discharge hose 17 bar; according to EC1935/2004, EU 10/2011, FDA, BfR, USDA and 3A



Characteristics

Series: Nutralon

Application

- highly flexible discharge hose for foodstuffs: suitable for transfer of milk products, animal fats, vegetable oils, fruit juices, etc.
- easy to clean because of the smooth bore
- also suitable for low pressure steam as cleaning hose
- crush resistant by trucks
- suitable for light under pressure; by suction applications
- by suction applications to 90% see the SD type with steel spiral
- Recommended in: Food & Beverages

Technical Information

Temperature range

- -30 °C to +100 °C
- steam cleaning up to 130 °C (max. 20 minutes without pressure)

Burst pressure

- minimum 68 bar
- safety factor 4:1

Construction

Tube

- white NBR rubber
- smooth, homogeneous and seamlessly extruded
- tasteless and odorless, phthalate and plasticiser free
- resistant to animal fats and vegetable oils
- resistant to most common cleaners

Reinforcement

- 2 braided synthetic fabrics, heat resistant
- kink resistant
- light vacuum resistant

Cover

- blue CR rubber
- smooth with cloth impression
- superior abrasion, weather and ozone resistance
- resistant to animal fats and vegetable oils

- non marking

Execution

Branding

- white marking with text: "GOODALL NUTRALON - FOOD 17 BAR - 250 PSI"
- imprinted text: "N2920 - NUTRALON - DN * - 17 BAR - 250 PSI - MEETS FDA, BFR, EC1935/2004, 3A 18.0 CLASSI & USDA REQUIREMENTS - MFR C-Y-M - MADE IN CANADA 10001"

Connections

- DIN 11851, BSM/RJT, SMS, IDF, DS, DIN 11864, Tri-clamp, but also flanges, TW couplings, Eritite (Cam & Groove) couplings, etc.

Assembly

- ferrules or safety clamps

Approval

Approvals/regulations

- EC1935/2004 - EU 10/2011 A,B,C,D1,D2,E (tested by an independent laboratory)
- FDA 21 CFR 177.2600
- BfR
- USDA
- 3A (18.0 CLASS I)
- ADI-free

Options

Comments

- The EC1935/2004 - EU 10/2011 requires that the hose must be traceable. The Nutralon hoses are provided with batch numbers over the entire length of the hose.

Complete assembly

- ERIKS can assemble the Nutralon with sanitary swaged stainless steel couplings.

Options

- hydrostatic test report
- excellent laser engraving on marking ferrule
- rubber protection rings and rubber covered couplings
- stainless steel anti-kink hose

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	%	mm	m	kg/m	
13	5	23	17	68	50	90	40	0.57	12948412
19	6	31	17	68	50	125	40	0.67	12948413
25	6	37	17	68	50	150	40	0.8	12948414

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.