



MECAFRANCE Ball valve Type: 3461 Stainless steel Pneumatic operated Single acting, spring closing Internal thread (BSPP) PN50 to PN100

Characteristics

Type: 3461

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 3-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Internal thread (BSPP)

Actuator: Pneumatic operated

Operating principle: Single acting, spring closing

Top flange standard: ISO 5211


Tertiary spindle seal material: RPTFE

Body seal: PTFE/Graphite

Actuator material: Aluminum anodized

Application

- Recommended in: Food & Beverages, Food primary processes (contact with food)



Nominal inner diameter	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/2" [15]	PN100	Manufacturer standard	SAF05	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054737
3/4" [20]	PN100	Manufacturer standard	SAF10	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054739
1" [25]	PN100	Manufacturer standard	SAF15	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054740
1.1/4" [32]	PN63	Manufacturer standard	SAF15	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054742
1.1/2" [40]	PN63	Manufacturer standard	SAF20	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054741
2" [50]	PN50	Manufacturer standard	SAF25	AMG	Full bore	1.4408	PTFE	1.4404	RPTFE	10054743

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.