



BURKERT Globe valve Type 3118 series 2012 stainless steel entry above the valve pneumatic flange EN (DIN) PN25

Characteristics

Function: Two-way valve
Norm: EN (DIN)
Construction type: Straight
Housing material: Stainless steel
Material quality: 1.4404
Process connection: Flange
Standard connection: EN 1092
Face to Face norm: EN 558, Series 1
Type of disc: Fixed disc
Actuation: Pressure above the valve
Type of actuator: Pneumatic piston
Function actuator: Spring closing
Position indicator: Yes
Stem seal type: Roof cuffs
Primary spindle seal material: PTFE/FPM
Material disc: 1.4401
Spindle material: 1.4401



Material bonnet: 1.4401
Bonnet gasket material: PTFE
Approvals: ATEX IECEx
Max. viscosity: 600 mm²/s
Medium temperature: -10 / 185 °C

Application

- Neutral gases.
- Steam.

Technical Information

- High flow capacity.
- Spring closure.
- Sealing in 2 directions.
- Process pressure above the valve.
- Optical level indicator.



Size table:

Actuator	A mm	c	ØD mm	H mm	L mm
E63	140	1/4" BSP	80	272	180
F80	150	1/4" BSP	101	299	200
F80	165	1/4" BSP	101	309	230
H125	185	1/4" BSP	157	429	290
H125	200	1/4" BSP	157	438	310
H125	235	1/4" BSP	157	449	350

Size process connection	Pressure rating	Kv value m ³ /h	Closing pressure bar	Type coding actuator	Pilot pressure	Actuator material	Ex-class	ATEX Zone	Ambient temperature °C	Article
DN32	PN25	19.5	16	E63	[Variable] - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIC T135 °C Db	Zone 1 / 21	-10 / 55	11815052

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size process connection	Pressure rating	Kv value m ³ /h	Closing pressure bar	Type coding actuator	Pilot pressure	Actuator material	Ex-class	ATEX Zone	Ambient temperature °C	Article
DN40	PN25	31	16	F80	[Variable] - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815053
DN50	PN25	45	16	F80	[Variable] - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815054
DN65	PN25	73	10	H125	[Variable] - 7 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815057
DN80	PN25	110	10	H125	[Variable] - 7 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815055
DN100	PN25	165	6	H125	[Variable] - 7 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815056

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.