


KROHNE Fig. 8223 electromagnetic flow meter

This is a dual-use or controlled item. When exporting this item outside the EU an export license is required from the regulatory authorities.



Characteristics

Series: PFA

Type: 8223

Adjustable measuring range: Yes

Calibration: Water

Accuracy: Down to 0.4 % of the measured value ± 1 mm/s

Relative repeat accuracy: ± 0.1 % Of the measured value - minimum 1 mm/s

Process connection: Clamping flange

Supply voltage: 100 - 230V AC

Electrical connection: Cable screw gland M20 x 1,5

Electricity consumption: 22 VA [AC] / 12 W [DC]

Impedance: 1000 Ω

Degree of protection (IP) of measuring head: IP66/
IP67

Degree of protection (IP) of evaluation electronic:
IP66/IP67

Display: Yes

Characteristics (2)

LED status indication: No

Material measuring tube: Stainless steel

Lining material: PFA

Material electrodes: Hastelloy C

Material switch housing: Aluminium

Max. pressure: 16 bar

Minimum medium conductivity: Standard ≥ 5 $\mu\text{S/cm}$

- demineralized water ≥ 20 $\mu\text{S/cm}$

Medium temperature: -25 / 120 °C

Ambient temperature: -25 / 65 °C

Measuring range	Measuring unit	Size process connection	Output signal	Start output signal	Material housing	Article
0 / 24	m ³ /h	DN40	4 - 20 mA And pulse	1.4 m ³ /h	Forged iron	12970304
0 / 150	m ³ /h	DN100	4 - 20 mA And pulse	8.5 m ³ /h	Sheet steel	12970307

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.