



ECON® Spring-loaded safety valve Type 1515 steel low-lifting internal/external thread

Type 1515 low-light safety device in a right-angled design.
The set pressure must be specified when ordering.

Characteristics

Type: 1515
Model: Spring-loaded safety valve
Construction type: Angle Pattern
Housing material inlet side: Steel
Material quality inlet side: St 52-3 N [1.0576]
Housing material outlet side: Steel
Material quality outlet side: St 52-3 N [1.0576]
Connection inlet side: External thread [NPT]
Standard connection inlet side: ISO 228-1
Connection outlet side: Internal thread [NPT]
Standard connection outlet side: ISO 228-1
Blow-off characteristic: Low-lifting
Gastight valve: Yes
Spring cap, closed: Yes
Material spring bonnet: St 52-3 N [1.0576]

Material disc: 1.4021
Seat material: 1.4057
Spring material: Spring steel
Spindle material: 1.4057
Medium temperature: 0 / 200 °C

Application


- Liquids [thermal expansion].
- Also suitable as an overflow.

Approval

- PED-2014/68/EC-certified.

Options

- Available with Lloyds adjustment certificate.
- Optionally available with inner wire connection in NPT.



Size table:

DN	d0	L1	L2	L3	H	Weight
mm	mm	mm	mm	mm	mm	kg
3/8"	8	45	48	15	128	1.02
1/2"	10	45	48	15	128	1.04
3/4"	15	57	56	18	129	1.64
1"	20	62	62	22	129	2
1.1/4"	25	67	70	25	142	2.6
1.1/2"	30	78	72	25	145	4.3
2"	40	90	85	28	160	5.8

Nominal inner diameter inlet side	Nominal inner diameter outlet side	Adjustment range	Valve bore	Valve lifter	Sealing	Article
		bar	mm			
3/8" [10]	3/8" [10]	5 / 10	8	No	Metal	13479575

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Safety Valves | Spring loaded safety valves with threaded connection

Nominal inner diameter inlet side	Nominal inner diameter outlet side	Adjustment range	Valve bore	Valve lifter	Sealing	Article
		bar	mm			
3/8" [10]	3/8" [10]	20 / 42	8	No	Metal	13479577
3/8" [10]	3/8" [10]	10 / 20	8	No	Metal	13479576
3/8" [10]	3/8" [10]	1 / 5	8	No	Metal	13479574
3/8" [10]	3/8" [10]	1 / 5	8	No	Metal	13479602
3/8" [10]	3/8" [10]	20 / 42	8	No	Metal	13479605
3/8" [10]	3/8" [10]	5 / 10	8	No	Metal	13479603
3/8" [10]	3/8" [10]	10 / 20	8	No	Metal	13479604
1/2" [15]	1/2" [15]	10 / 20	10	No	Metal	13479580
1/2" [15]	1/2" [15]	5 / 10	10	No	Metal	13479579
1/2" [15]	1/2" [15]	20 / 42	10	No	Metal	13479581
1/2" [15]	1/2" [15]	1 / 5	10	No	Metal	13479578
1/2" [15]	1/2" [15]	10 / 20	10	No	Metal	13479608
1/2" [15]	1/2" [15]	5 / 10	10	No	Metal	13479607
1/2" [15]	1/2" [15]	1 / 5	10	No	Metal	13479606
1/2" [15]	1/2" [15]	20 / 42	10	No	Metal	13479609
3/4" [20]	3/4" [20]	20 / 42	15	No	Metal	13479585
3/4" [20]	3/4" [20]	10 / 20	15	No	Metal	13479584
3/4" [20]	3/4" [20]	1 / 5	15	No	Metal	13479582
3/4" [20]	3/4" [20]	5 / 10	15	No	Metal	13479583
3/4" [20]	3/4" [20]	10 / 20	15	No	Metal	13479612
3/4" [20]	3/4" [20]	20 / 42	15	No	Metal	13479613
3/4" [20]	3/4" [20]	1 / 5	15	No	Metal	13479610
3/4" [20]	3/4" [20]	5 / 10	15	No	Metal	13479611
1" [25]	1" [25]	1 / 5	20	No	Metal	13479586
1" [25]	1" [25]	5 / 10	20	No	Metal	13479587
1" [25]	1" [25]	20 / 42	20	No	Metal	13479589
1" [25]	1" [25]	10 / 20	20	No	Metal	13479588
1" [25]	1" [25]	5 / 10	20	No	Metal	13479615
1" [25]	1" [25]	1 / 5	20	No	Metal	13479614
1" [25]	1" [25]	20 / 42	20	No	Metal	13479617
1" [25]	1" [25]	10 / 20	20	No	Metal	13479616
1.1/4" [32]	1.1/4" [32]	20 / 42	25	No	Metal	13479593
1.1/4" [32]	1.1/4" [32]	1 / 5	25	No	Metal	13479590
1.1/4" [32]	1.1/4" [32]	10 / 20	25	No	Metal	13479592
1.1/4" [32]	1.1/4" [32]	5 / 10	25	No	Metal	13479591
1.1/4" [32]	1.1/4" [32]	20 / 42	25	No	Metal	13479621
1.1/4" [32]	1.1/4" [32]	5 / 10	25	No	Metal	13479619
1.1/4" [32]	1.1/4" [32]	1 / 5	25	No	Metal	13479618
1.1/4" [32]	1.1/4" [32]	10 / 20	25	No	Metal	13479620
1.1/2" [40]	1.1/2" [40]	20 / 42	30	No	Metal	13479597
1.1/2" [40]	1.1/2" [40]	1 / 5	30	No	Metal	13479594
1.1/2" [40]	1.1/2" [40]	5 / 10	30	No	Metal	13479595
1.1/2" [40]	1.1/2" [40]	10 / 20	30	No	Metal	13479596
1.1/2" [40]	1.1/2" [40]	1 / 5	30	No	Metal	13479622
1.1/2" [40]	1.1/2" [40]	20 / 42	30	No	Metal	13479625
1.1/2" [40]	1.1/2" [40]	5 / 10	30	No	Metal	13479623
1.1/2" [40]	1.1/2" [40]	10 / 20	30	No	Metal	13479624
2" [50]	2" [50]	10 / 20	40	No	Metal	13479600
2" [50]	2" [50]	1 / 5	40	No	Metal	13479598
2" [50]	2" [50]	20 / 42	40	No	Metal	13479601
2" [50]	2" [50]	5 / 10	40	No	Metal	13479599
2" [50]	2" [50]	5 / 10	40	No	Metal	13479627

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Safety Valves | Spring loaded safety valves with threaded connection

Nominal inner diameter inlet side	Nominal inner diameter outlet side	Adjustment range bar	Valve bore mm	Valve lifter	Sealing	Article
2" (50)	2" (50)	10 / 20	40	No	Metal	13479628
2" (50)	2" (50)	1 / 5	40	No	Metal	13479626

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.