



MECAFRANCE Ball valve Type: 3460 Stainless steel Butt weld EN ISO 1127-1 PN50 to PN100

Characteristics

Type: 3460
Norm: EN (DIN)
Construction type: 2-way
Housing construction: 3-part
Housing material: Stainless steel
Material quality: 1.4408
Wall thickness, connection: 2 mm
Connection: Butt weld
Standard welding connection: EN ISO 1127-1

Top flange standard: ISO 5211

Bore: Full bore

Tertiary spindle seal material: RPTFE

Application

- Recommended in: Food & Beverages, Food primary processes (contact with food)

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/4" [8]	13.5	PN100	Manufacturer standard	Handle	F03	1.4408	PTFE	1.4404	RPTFE	11286294
3/8" [10]	17.2	PN100	Manufacturer standard	Handle	F03	1.4408	PTFE	1.4404	RPTFE	10055485
1/2" [15]	21.3	PN100	Manufacturer standard	Handle	F03	1.4408	PTFE	1.4404	RPTFE	12188977
3/4" [20]	26.9	PN100	Manufacturer standard	Handle	F04	1.4408	PTFE	1.4404	RPTFE	12188978
1" [25]	33.7	PN80	Manufacturer standard	Handle	F04	1.4408	PTFE	1.4404	RPTFE	12188979
1.1/4" [32]	42.4	PN63	Manufacturer standard	Handle	F05	1.4408	PTFE	1.4404	RPTFE	12188980
1.1/2" [40]	48.3	PN63	Manufacturer standard	Handle	F05	1.4408	PTFE	1.4404	RPTFE	12188981
2" [50]	60.3	PN50	Manufacturer standard	Handle	F07	1.4408	PTFE	1.4404	RPTFE	12188982
2" [50]	60.3	PN80					TFM 1600			13405014

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.