


GOODALL Coupling GDF-M-C



Characteristics

Type of component: Hose tail coupling

Material: AISI 316

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: SMS

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 205 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				13527823
				13506277
DN15	DN12	40	580	13704443
DN20	DN19	40	580	13704444
DN20	DN25	40	580	14104856
DN25	DN25	40	580	13704445
DN32	DN32	40	580	13704446
DN40	DN38	40	580	13704447
DN32	DN38	40	580	13530601
DN50	DN50	25	362	13704448
DN65	DN63	25	362	13704449
DN80	DN75	25	362	13704450
DN100	DN100	25	362	13704451
1"	DN25	40	580	13704459
1.1/4"	DN32	40	580	13704460
1.1/2"	DN38	40	580	13704461
2"	DN50	40	580	13704462
2.1/2"	DN63	25	362	13704463
3"	DN75	25	362	13704464
4"	DN100	25	362	13704465

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.