

ECON® Ball valve Type: 7622FS Steel Fire safe Butt weld B16.25 S40 Class 600



Characteristics

Type: 7622FS
Norm: ASME
Construction type: 2-way
Housing construction: 3-part
Housing material: Steel
Material quality: ASTM A216 WCB
Surface protection: Chemical blackened
Connection: Butt weld
Standard welding connection: B16.25 S40
Top flange standard: ISO 5211 Direct Mount
With locking device: No
Material ball: ASTM A351 CF8M
Seat material: TF 4103
Spindle material: ASTM A276 316 Grade S
Primary spindle seal material: RPTFE
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: Graphite
Body seal: Graphite
Material connection piece: ASTM A216 WCB
Minimum medium temperature (continuous): -29 °C
Maximum medium temperature (continuous): 220 °C
Fire safe: Yes
Pressure relief:

Application

- Industrial and maritime applications.
- Liquid and gaseous media.
- Recommended in: Chemical

Technical Information

- Connection according to ASME B16.25 S40.
- Floating ball.
- Pressure class: Class 600.
- With direct-mount top flange according to ISO 5211.
- Closed neck design with leak detection opening.
- Equipped with a robust lever.
- Average temperature for a tap with standard TF 4103 seats: -29°C/+220°C. Up to a maximum of 250° C for taps with TF 4215 seats.

Construction

- Three-part housing construction.
- Wall thickness according to EN 12516-1 and ASME B16.34.
- Full or reduced bore.
- Design with antistatic equipment between ball and housing.

Approval

- Fire-safe according to ISO 10497 (third edition) and API 607 (seventh edition).
- Type approval from Lloyd's Register.
- Safety integrity level (SIL) 2.

Options

- Design with worm gearbox, pneumatic, electric or hydraulic drives.
- Position feedback for manual and automatic valves.
- Available with different seat materials such as TF 4215, TFM 1600 and PEEK.
- Fire-safe design available.
- Stainless steel extended spindle for insulation.
- With connection for earthing.
- With 30°, 60° or 90° V-shaped ball bore for modulating applications.
- Connections with NPT thread according to ASME B1.20.1, BSPP thread according to ISO 228-1, socket weld according to ASME B16.11 or EN 12760, and butt weld according to EN 12627.

Size table:

DN	Full bore	d mm	L mm	H mm	M mm	C mm	Weight kg
1/4" [8]	Yes	15	71	83	140	13.7	0.9
3/8" [10]	Yes	15	71	83	140	17.1	0.9
1/2" [15]	Yes	15	72	83	140	21.3	1
3/4" [20]	No	15	72	83	140	26.7	1
3/4" [20]	Yes	20	97	88	140	26.7	1.5
1" [25]	No	20	97	88	140	33.4	1.5
1" [25]	Yes	25	109	97	190	33.4	2
1.1/4" [32]	No	25	109	97	190	42.2	2
1.1/4" [32]	Yes	31.8	118	103	190	42.2	3
1.1/2" [40]	No	31.8	118	103	190	48.3	3
1.1/2" [40]	Yes	38	129	148	290	48.3	4.5
2" [50]	No	38	129	148	290	60.3	4.5
2" [50]	Yes	50	145	157	209	60.3	6.5
2.1/2" [65]	No	50	145	157	290	75	6.5

Pressure and temperature range

Seat material + DN full bore	-29	50	100	150	200	250	300	[°C]
TF4103 & TFM1600 1/4" - 1"	102.1	100.2	68	34	0	-	-	[bar]
TF4215 1/4" - 1"	102.1	100.2	93.2	63	32	0	-	[bar]
PEEK 1/4" - 1"	102.1	100.2	93.2	77	48	18	0	[bar]
TF4103 & TFM1600 1.1/4" - 1.1/2"	80	80	55	28	0	-	-	[bar]
TF4215 1.1/4" - 1.1/2"	80	80	80	55	28	0	-	[bar]
PEEK 1.1/4" - 1.1/2"	80	80	80	77	48	18	0	[bar]
TF4103 & TFM1600 2"	76	76	53	27	0	-	-	[bar]
TF4215 2"	76	76	76	51	25	0	-	[bar]
PEEK 2"	76	76	76	76	47	18	0	[bar]

Nominal inner diameter	External tube diameter of connection mm	Wall thickness, connection mm	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Mounting flange 2	Bore	Maximum operating pressure bar	Article
1/4" [8]	13.7	2.25	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	102	13708520
3/8" [10]	17.1	2.3	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	102	13708521
1/2" [15]	21.3	2.75	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	102	13559672
3/4" [20]	26.7	2.85	Class 600	Manufacturer standard	Handle	F03	F04	Reduced bore	102	14256505

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	External tube diameter of connection mm	Wall thickness, connection mm	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Mounting flange 2	Bore	Maximum operating pressure bar	Article
3/4" [20]	26.7	2.85	Class 600	Manufacturer standard	Handle	F03	F04	Full bore	102	13559673
1" [25]	33.4	3.4	Class 600	Manufacturer standard	Handle	F03	F04	Reduced bore	102	14256506
1" [25]	33.4	3.4	Class 600	Manufacturer standard	Handle	F04	F05	Full bore	102	13559674
1.1/4" [32]	42.2	3.55	Class 600	Manufacturer standard	Handle	F04	F05	Reduced bore	102	14256507
1.1/4" [32]	42.2	3.55	Class 600	Manufacturer standard	Handle	F04	F05	Full bore	80	13559675
1.1/2" [40]	48.3	3.7	Class 600	Manufacturer standard	Handle	F04	F05	Reduced bore	80	14256508
1.1/2" [40]	48.3	3.7	Class 600	Manufacturer standard	Handle	F07		Full bore	80	13559676
2" [50]	60.3	3.9	Class 600	Manufacturer standard	Handle	F07		Reduced bore	80	14256509
2" [50]	60.3	3.9	Class 600	Manufacturer standard	Handle	F07		Full bore	76	13559677
2.1/2" [65]	75	6.25	Class 600	Manufacturer standard	Handle	F07		Reduced bore	76	14256510

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.