



Temporary filter Type: 1028 Stainless steel

Characteristics

Type: 1028

Material: Stainless steel

Material quality: SS304

Pressure rating: PN16

Pressure rating flange: PN16 - Class 150

Application

- For protecting pumps and holding welding attachments, bolts, nuts etc.
- Horizontal piping
- Vertical piping with downwards flow
- Suction and delivery piping

Technical Information

- The temporary filter is specifically designed for use during commissioning of new systems and their subsequent removal.
- Mount with the tip of the screen in the opposite direction to the flow.
- Mounting between flanges in accordance with EN 1092-1, form B1 (PN 10/PN 16) and ASME B16.5, Class 150

Options

- Available with other perforations
- Available with larger openings

Nominal inner diameter	Perforation size mm	Article
DN25	1	14154711
DN25	3	14154712
DN32	1	14154723
DN32	3	14154724
DN40	1	14154725
DN40	3	14154726
DN50	1	14154727
DN50	3	14154728
DN65	1	14154729
DN65	3	14154730
DN80	1	14154731
DN80	3	14154732
DN100	1	14154733
DN100	3	14154734
DN125	1	14154735
DN125	3	14154736
DN150	1	14154737
DN150	3	14154738
DN200	1	14154739
DN200	3	14154740
DN250	1	14154741
DN250	3	14154742
DN300	1	14154743
DN300	3	14154744

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.