


OLEODINAMICA MARCHESINI High-pressure/low-pressure valve CETOP, VABP FL series




In a circuit which is supplied by 2 parallel pumps, this valve unloads the larger pump to tank once the setting has been reached. From this point the actuator will only be supplied by the smaller pump at a higher pressure, therefore consuming less energy. It is designed for direct flange mounting onto Cetop solenoid valves.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- Cetop mounting interface.



Characteristics

Version: Inline mounting

Size: CETOP 7

Material: Steel

Max. operating pressure bar	Max. oilflow l/min	Adjustment range	Connections	Article
350	40 + 20	AP 50 - 350 bar, BP 20 - 80 bar	AP 1/4" BSP, BP 3/8" BSP, A,B,T 1/2" BSP	14229149
350	50 + 30	AP 50 - 350 bar, BP 20 - 80 bar	AP 3/8" BSP, BP,U 1/2" BSP, T 3/4" BSP	14229152
350	100 + 40	AP 50 - 350 bar, BP 20 - 80 bar	AP 1/2" BSP, BP,U 3/4" BSP, T 1" BSP	14229153

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.