



OLEODINAMICA MARCHESINI Fixed power distributor type DFL

These valves are used when two equal actuators, that are not mechanically coupled, supplied by the same pump and controlled by a single valve, must move simultaneously both in extension and retraction.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- Pipemounting: BSP ports.



Characteristics

Type: Inline mounting

Max. operating pressure: 250 bar

Volume flow l/min	Connections	Material	Article
1-3	C,A,B: 3/8" BSP	Steel	14229138
3-6	C,A,B: 3/8" BSP	Steel	14229139
6-10	C,A,B: 3/8" BSP	Steel	14229140
10-20	C,A,B: 3/8" BSP	Steel	14229141
20-32	C,A,B: 3/8" BSP	Steel	14229142
25-40	C: 1/2"BSP, A,B: 3/8" BSP	Steel	14229143
40-60	C: 1/2"BSP, A,B: 3/8" BSP	Steel	14229144
60-80	C: 1/2"BSP, A,B: 3/8" BSP	Steel	14229145
80-100	C: 3/4"BSP, A,B: 1/2" BSP	Steel	14229146
100-120	C: 1" BSP, A,B: 3/4" BSP	Steel	14229147
120-150	C: 1" BSP, A,B: 3/4" BSP	Steel	14229148

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.