

FACOM Protwist slotted screwdriver type AT.VE

STANDARDS: NF ISO 2380-1, NF ISO 2380-2, NF EN 60900, ISO 2380-1, ISO 2380-2, EN 60900, DIN ISO 2380-1, DIN ISO 2380-2, DIN EN 60900/ASME B107.600

- For your safety, each screwdriver is tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.

-1.000 Volt sheathed round blade.

-Milled blade: --> 5.5 mm included.

-Fillet blade: 6.5 --> 12 mm.

-Bi-material grip resists to impacts, abrasion, and chemicals.

-New chemical resistant handle with "power" channel for higher torque transfer.

-New softer handle material for improved comfort.



Blade width mm	Blade length mm	Article
2	75	13606067
2.5	75	13547496
3	75	13600536
3	100	13606070
3.5	100	13581373
4	100	13613945
4	150	13600537
5.5	125	13600538
5.5	200	13574249
10	200	13628973

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.