



MHA ZENTGRAF 3-Way ball valve Series: BK3 Steel Internal thread (BSPP) PN315/500

Characteristics

Series: BK3
Norm: EN (DIN)
Construction type: 3-way
Housing construction: 4-part
Housing material: Steel
Material quality: Forged steel
Surface protection: Zinc Plated
Connection: Internal thread (BSPP)

Characteristics [2]

Seat material: POM
Spindle material: Steel
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Ball bore	Material ball	Secondary spindle seal material	Body seal	Weight kg	Article
1/8" [4]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	0.4	14288520
1/8" [4]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	0.4	14288519
1/4" [6]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	0.46	14288513
1/4" [6]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	0.46	14288512
3/8" [10]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	0.6	14288593
3/8" [10]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	0.6	14288592
1/2" [13]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	0.7	14288505
1/2" [13]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	0.7	14288503
3/4" [20]	ISO 228-1	PN315	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	1.8	14288585
3/4" [20]	ISO 228-1	PN315	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	1.8	14288583
1" [25]	ISO 228-1	PN315	Manufacturer standard	Handle	L-bore	Steel	NBR	NBR	2.4	14601670
3/8" [10]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	0.6	14613066
3/8" [10]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	FPM (FKM)	FPM (FKM)	0.6	14613067
1/2" [13]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	0.7	14613077
1/2" [13]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	FPM (FKM)	FPM (FKM)	0.7	14613078
3/4" [20]	ISO 228-1	PN315	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	1.8	14613084
3/4" [20]	ISO 228-1	PN315	Manufacturer standard	Handle	T-bore	Steel	FPM (FKM)	FPM (FKM)	1.8	14613085
1" [25]	ISO 228-1	PN315	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	2.4	14613092
1" [25]	ISO 228-1	PN315	Manufacturer standard	Handle	T-bore	Steel	FPM (FKM)	FPM (FKM)	2.4	14613093
1" [25]	ISO 228-1	PN315	Manufacturer standard	Handle	T-bore	Steel	NBR	NBR	2.4	14613094
1/8" [4]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	0.4	14613097
1/4" [6]	ISO 228-1	PN500	Manufacturer standard	Handle	L-bore	Steel	FPM (FKM)	FPM (FKM)	0.46	14613101
1/4" [6]	ISO 228-1	PN500	Manufacturer standard	Handle	T-bore	Steel	FPM (FKM)	FPM (FKM)	0.46	14613102

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.