


Pressure reducing valve Type 8938 stainless steel flange

A full stainless steel direct acting pressure reducing valve, especially designed for steam up to 200 °C. Also very much suited for applications involving liquids, air and neutral gases.

Due to a specially developed interior design fluctuating inlet pressures do not influence the reduced pressure because of the inbuilt pressure relief, which guarantees a constant outlet pressure. The piston operated trim makes it this pressure reducing valve very robust, and a long lifespan is guaranteed.



Characteristics

Series: DRV 838-D

Type: 8938

Model: Direct-acting

Connection: Flange

Maximum inlet pressure: 16 bar

Medium temperature: 20 / 200 °C

Suitable for gases: 1

Housing material: Stainless steel

Material quality: 1.4408

Material disc: 1.4404

Seat material: 1.4404

Membrane material: 1.4404

Spring material: Stainless steel

Material spring bonnet: 1.4408

With couplers: No

Backflow preventer: No

Technical Information

- Downstream pressure ranges:
- 0.3 - 2.0 bar.
- 2.0 - 5.0 bar.
- 4.0 - 10.0 bar.
- Maximum pressure reducing ratio 53 : 1.
- Capacity rangeability ratio 20 : 1.
- Minimum reduced pressure 0.3 bar.
- Minimum pressure difference 1 bar.

Approval


- CE DGRL 2014/68/EU.
- DNV GL.
- Lloyd's Register.
- Bureau Veritas.
- American Bureau of Shipping.
- CCS.

Application

- Steam up to 200 °C.
- Hot water.
- Various fluids (please check on chemical resistancy).
- Air.
- Neutral gases.

Size table:

DN	P bar	A mm	H mm	H1 mm	L mm	Weight kg
DN15	0.3 / 2	95	150	48	130	3.8
DN15	4 / 10	95	116	48	130	2.9
DN15	2 / 5	95	116	48	130	2.9
DN20	4 / 10	105	116	53	150	3.6
DN20	2 / 5	105	116	53	150	3.6
DN20	0.3 / 2	105	150	53	150	4.6
DN25	0.3 / 2	115	151	58	160	5.8
DN25	4 / 10	115	116	58	160	4.9
DN25	2 / 5	115	116	58	160	4.8
DN32	2 / 5	140	116	70	180	6.2
DN32	0.3 / 2	140	151	70	180	7
DN32	4 / 10	140	116	70	180	6.2
DN40	4 / 10	200	219	75	200	9.8
DN40	2 / 5	200	219	75	200	9.7
DN40	0.3 / 2	200	262	75	200	13
DN50	4 / 10	165	219	83	230	11.6
DN50	0.3 / 2	165	262	83	230	14.5
DN50	2 / 5	165	219	83	230	11.5



Nominal inner diameter	Capacity type	Kvs value m³/h	Reduced pressure range bar	Article
DN15	Standard	3.6	0.3 / 2	14279660
DN15	Standard	3.6	4 / 10	14279672
DN15	Standard	3.6	2 / 5	14279666
DN20	Standard	4.1	4 / 10	14279673
DN20	Standard	4.1	2 / 5	14279667
DN20	Standard	4.1	0.3 / 2	14279661
DN25	Standard	5.3	0.3 / 2	14279662
DN25	Standard	5.3	4 / 10	14279674
DN25	Standard	5.3	2 / 5	14279668
DN32	Standard	5.6	2 / 5	14279669
DN32	Standard	5.6	0.3 / 2	14279663
DN32	Standard	5.6	4 / 10	14279675
DN40	Standard	13.3	4 / 10	14279676
DN40	Standard	13.3	2 / 5	14279670
DN40	Standard	13.3	0.3 / 2	14279664
DN50	Standard	14	4 / 10	14279677
DN50	Standard	14	0.3 / 2	14279665
DN50	Standard	14	2 / 5	14279671

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.