

EZO Miniature ball bearing closure on one side

Miniature ball bearings are single-row deep groove ball bearings with a bore diameter of up to 10 mm. Single-row deep groove ball bearings are extremely versatile. They are simple in design, suitable for high to very high speeds, very robust and thus low-maintenance. Thanks to the deep grooves and the close contact between the grooves and the balls, deep groove ball bearings are extremely well suited to tolerate both radial loads and axial loads in both directions, even at high speeds. Both open (unsealed) and sealed versions of the miniature ball bearings are available.

Bearing with cover plates Z:

The cover plates, manufactured from sheet steel, are primarily suited to applications where the i-race of the bearing rotates. There is a sealing gap between the outer edge of the plate and the i-race. The clearance between the cover plate and the i-race is designed in such a way that no contact can be made, even if the bearing exhibits a large amount of radial play. To prevent corrosion, the cover plates are galvanized.

Characteristics

Series: 60 **Type:** 608

Execution: Single row

Material: Steel

Sealing: Closure on one side

With flange: No

Manufacturer ID	Inner diameter	Outer diameter	Width	Internal clearance	Cage	Article
	mm	mm	mm			
625 Z	5	16	5	CN (normal)	Steel	13550076
626 Z	6	19	6	CN (normal)	Steel	13550079
607 Z	7	19	6	CN (normal)	Steel	13550064
608 Z	8	22	7	CN (normal)	Steel	13550067

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



PR1579278047106713_EN_18.05.2024