



ECON® Pneumatic actuator Type: 7902 Aluminium Double acting



Characteristics

Type: 7902
Transmission: Quarter turn
Operating principle: Double acting
Top flange standard: ISO 5211
Square type: Double square
Material housing: Aluminium
Housing surface protection: Anodized
Material cover: Aluminium + Epoxy
Spindle material: Steel
Material bolts: Stainless steel
Top flange connection: NAMUR [VDI/VDE 3845]
Shaft height: 30 mm
With mechanical setting indicator: Yes
Puck for sensor: Yes
Connection standard air supply: NAMUR 2 [VDI/VDE 3845]

Application

- The Econ® Rack & Pinion pneumatic actuators are ideal for the on/off or continuous operation of plug, butterfly and ball valves.

Technical Information

- Double acting output torque up to 6.421 Nm [56.831 in-lb].
- Working temperature -30 °C to 100 °C [-22 °F to 212 °F].
- Angle of rotation is 90° ±5° by means of external travel stops [between 85° and 95°].
- Guaranteed service life of 500.000 cycles.
- Anti-friction sliding bearings provide long life without maintenance.
- Hard anodized aluminum body.
- Serialnumbers on body part for traceability.
- End caps denote spring return or double acting set up.
- Multifunction position indicator suitable for mechanical limit switches or dual proximity sensors.

Construction

- Anti-blowout pinion design.
- Mounting and drive connections to ISO 5211 and DIN 3337.
- Air supply and top flange connection according to NAMUR VDI/VDE 3845.
- Anti-corrosive coatings according to EN-ISO 12944-2 C3.

Approval


- Safety integrity rating IEC 61508 SIL 2 [SIL 3 in redundant configuration].
- Classified for use in potentially explosive atmospheres as Group II, Category 2, suitable for zones 1, 2, 21 and 22 in accordance with Annex VIII of Directive 2014/34/EU [ATEX].
- In accordance with Pressure Equipment Directive [PED] 2014/68/EU, Econ® Rack & Pinion actuators are classified as follows: > Size DA/SR 10 to 850 - Category SEP > Size DA/SR 1200 to 4000 - Category I.

Options

- Low temperature version down to -60 °C [-76 °F].
- High temperature version up to +150 °C [302 °F].
- Stroke limitation up to 100%.
- Safety lockout device.
- Passivation choices include: Epoxy coating, Polyurethane coating, PTFE coating, Nickel plating [Corrosion categories according to EN-ISO 12944-2 C4, C5I or C5M].
- Stainless steel pinion [Grade 304 and 316].
- Maximum working pressure 8 bar [120 psi].

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size table:



Weight
kg
0.5
1
1.1
2
3
3.8
5.1
6.1
11
13.8
20.2
28.5
40
52.6
73.6
108
147
221

Model	Mounting flange	Mounting flange 2	Stem shape	Square dimensions	Double-acting torque 6 bar	Distance of mounting holes	Square depth	Air supply connection	Weight	Article
				mm	Nm		mm		kg	
DA10	F03		Double square	9	7.1	50x30	13	1/8" (6) internal thread [BSPP]	0.5	14442128
DA15	F04		Double square	9	7.1	80x30	13	1/8" (6) internal thread [BSPP]	1	14442129
DA20	F04		Double square	9	21.6	80x30	14	1/4" (8) internal thread [BSPP]	0.5	14442131
DA20	F03	F05	Double square	11	21.6	80x30	14	1/4" (8) internal thread [BSPP]	1.1	14442130
DA40	F05	F07	Double square	14	43.9	80x30	18	1/4" (8) internal thread [BSPP]	2	14442133
DA80	F05	F07	Double square	14	68.2	80x30	20	1/4" (8) internal thread [BSPP]	3	14442134
DA100	F05	F07	Double square	17	100.1	80x30	23	1/4" (8) internal thread [BSPP]	3.8	14442135
DA130	F05	F07	Double square	17	140.6	80x30	32	1/4" (8) internal thread [BSPP]	5.1	14442136
DA200	F07	F10	Double square	22	183.3	80x30	25	1/4" (8) internal thread [BSPP]	6.1	14442137
DA300	F07	F10	Double square	22	327.4	80x30	35	1/4" (8) internal thread [BSPP]	11	14442138

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Model	Mounting flange	Mounting flange 2	Stem shape	Square dimensions mm	Double-acting torque 6 bar Nm	Distance of mounting holes	Square depth mm	Air supply connection	Weight kg	Article
DA500	F10	F12	Double square	27	483	80x30	35	1/4" (8) internal thread [BSPP]	13.8	14442139
DA850	F10	F12	Double square	27	670.4	80x30	40	1/4" (8) internal thread [BSPP]	20.2	14442140
DA1200	F10	F14	Double square	36	1053.9	130x30	45	1/4" (8) internal thread [BSPP]	28.5	14442141
DA1200	F12		Double square	27	1053.9	130x30	45	1/4" (8) internal thread [BSPP]	28.5	14442142
DA1750	F14		Double square	36	1471.3	130x30	45	1/4" (8) internal thread [BSPP]	40	14442143
DA1750	F12		Double square	27	1471.3	80x30	45	1/4" (8) internal thread [BSPP]	40	14442144
DA2100	F16		Double square	46	2282	130x30	55	1/2" (12)	52.6	14442145
DA2100	F14		Double square	36	2282	130x30	55	1/2" (12)	52.6	14442146
DA2500	F16		Double square	46	3209	130x30	55	1/2" (12)	736	14442147
DA4000	F16		Double square	55	4128.8	130x30	70	1/2" (12)	108	14442148
DA6000	F16	F25	Double square	55	6127.5	130x30	70	1/2" (12)	147	14442149
DA9000	F25		Double square	55	9337.1	130x30	70	1/2" (12)	221	14442150

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.