



FILTRATION GROUP Spin-On cartridge filter medium glass fibre series PX-SMX

Characteristics

Series: PX-...-SMX

Temperature range [°C]: -10 / 120 °C

Code digit	Size	Filter element material	Filter fineness µm	Permitted working pressure bar	Connection	Length of filter element mm	Outer diameter mm	Article
PX33-13-2-SMX3	100	Fiber glass	3	16	1.1/2-16 UNF	170	140	13521475
PX37-13-2-SMX3	160	Fiber glass	3	14	1.1/2-16 UNF	308	160	13521488
PX37-14-1-SMX3	160	Fiber glass	3	14	1.1/4" BSP	308	160	13521493
PX36-13-2-SMX3	130	Fiber glass	3	16	1.1/2-16 UNF	238	140	13521482
PX36-13-2-SMX6	130	Fiber glass	6	16	1.1/2-16 UNF	238	140	13521483
PX33-13-2-SMX6	100	Fiber glass	6	16	1.1/2-16 UNF	170	140	13521476
PX37-13-2-SMX6	160	Fiber glass	6	16	1.1/2-16 UNF	308	160	13521489
PX37-13-2-SMX10	160	Fiber glass	10	25	1.1/2-16 UNF	308	160	13521486
PX37-14-1-SMX10	160	Fiber glass	10	10	1.1/4" BSP	308	160	13521492
PX33-13-2-SMX10	100	Fiber glass	10	16	1.1/2-16 UNF	170	140	13521473
PX36-13-2-SMX10	130	Fiber glass	10	16	1.1/2-16 UNF	238	140	13521480
PX37-13-2-SMX25	160	Fiber glass	25	25	1.1/2-16 UNF	308	160	13521487

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.