

GOODALL Rubber hose White Guardian



Characteristics

Series: White Guardian

Application

- hot water and steam cleaning applications in the food industry
- suitable for use in dairies, slaughterhouses and in the food industry
- excellent to use on hose reels

Technical Information

Temperature range

- hot water up to +95 °C
- saturated steam up to +164 °C

Burst pressure

- minimum 60 bar
- safety factor hot water 3:1
- safety factor steam 10:1

Construction

Tube

- white EPDM rubber
- smooth
- non-contaminating formulation
- excellent resistance to the most common cleaning agents

Reinforcement

- multiple high-tensile spirally synthetic fabrics

Cover

- white EPDM rubber
- smooth, non-marking cover
- heat, abrasion, weather & ozone resistant
- resistant to vegetable oils and animal fats

Execution

Branding

- white longitudinal Mylar stripe: "GOODALL WHITE GUARDIAN - STEAM 6 BAR 164°C / 90 PSI 330°F"
- embossed strip: "GOODALL WHITE GUARDIAN 6bar [90PSI] 164°C [330°F] MAX TEMP OPEN STEAM - quarter/year"

Approval

- EC1935/2004
- FDA
- BfR
- ADI (Animal Derived Ingredient) free

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
13	6	25	20	60	100	40	0.48	10015268
19	7	33	20	60	160	40	0.73	10015269
25	7	39	20	60	200	40	0.85	10015270

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.