

HYPRESS Hydraulic hose textile reinforced 2TE

Characteristics

Series: 2TE

Material of inner wall: Oil resistant synthetic rubber

Material of outer wall: Synthetic rubber, abrasion, weather and ozon resistant

Quality cover: Standard

Temperature range [°C]: -40 / 100 °C

EN standard: EN 854-2TE



Code	Hose ID (DN)	Hose ID in	Outer diameter mm	Maximum operating pressure bar	Minimum burst pressure bar	Minimum bending radius mm	Outside wall colour	Weight kg/m	Article
2TE-03	DN05	3/16"	11.8	80	320	35	Black	0.118	14573458
2TE-04	DN06	1/4"	13.4	75	300	40	Black	0.14	14573459
2TE-05	DN08	5/16"	14.9	68	272	50	Black	0.154	14573460
2TE-06	DN10	3/8"	16.5	63	252	60	Black	0.179	14573461
2TE-08	DN12	1/2"	19.7	58	232	70	Black	0.226	14573462
2TE-10	DN16	5/8"	23.9	50	200	90	Black	0.312	14573473
2TE-12	DN19	3/4"	27	45	180	110	Black	0.342	14573474
2TE-16	DN25	1"	34.4	40	160	150	Black	0.483	14573475

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.