



MHA ZENTGRAF 3-Way ball valve Series: 3KH Steel Cutting ring, light (L) PN315/400/500

Characteristics

Series: 3KH
Construction type: 3-way
Housing material: Steel
Surface protection: Zinc Plated
Connection: Cutting ring, light (L)
Standard connection: DIN 2353 / ISO 8434-1
Seat material: POM

Characteristics (2)

Spindle material: Steel
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.7	14613106
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	2.7	14613107
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	2.7	14613108
DN10	12	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.7	14613109
DN13	15	M 22x1.5	PN400	Manufacturer standard	Handle	L-bore	NBR	NBR	5.1	14613124
DN13	15	M 22x1.5	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	5.1	14613125
DN16	18	M 26x1.5	PN400	Manufacturer standard	Handle	L-bore	NBR	NBR	4.7	14613131
DN16	18	M 26x1.5	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	4.7	14613132
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	6.7	14613136
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	6.7	14613137
DN20	22	M 30x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	6.7	14613138
DN32/25	35	M 45x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	8.3	14613148
DN32/25	35	M 45x2	PN315	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	8.3	14613149
DN32/25	35	M 45x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	8.3	14613150
DN32/25	35	M 45x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.3	14613151
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	8.2	14613159
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	8.2	14613160
DN25	28	M 36x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.2	14613161
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	1.6	14613168
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	1.6	14613169
DN04	6	M 12x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	1.6	14613170
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	1.6	14613182
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	1.6	14613183
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	1.6	14613184
DN06	8	M 14x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	1.6	14613185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.6	14613190
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	2.6	14613191
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	2.6	14613192
DN08	10	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.6	14613193

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.