



MHA ZENTGRAF 4-Way ball valve Series: 4KH Steel Cutting ring, heavy (S) PN315/400/500

Characteristics

Series: 4KH

Construction type: 4-way

Housing material: Steel

Surface protection: Zinc Plated

Connection: Cutting ring, heavy (S)

Seat material: POM

Spindle material: Steel

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.7	14613200
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	X-bore	NBR	NBR	2.7	14613201
DN13	16	M 24x1.5	PN400	Manufacturer standard	Handle	X-bore	FPM (FKM)	FPM (FKM)	4.8	14613214
DN13	16	M 24x1.5	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	4.8	14613215
DN13	16	M 24x1.5	PN400	Manufacturer standard	Handle	X-bore	NBR	NBR	4.8	14613216
DN16	20	M 30x2	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	4.8	14613223
DN16	20	M 30x2	PN400	Manufacturer standard	Handle	X-bore	NBR	NBR	4.8	14613224
DN20	25	M 30x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	6.7	14613227
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	X-bore	NBR	NBR		14613228
DN25	38	M 52x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.5	14613243
DN32/25	38	M 52x2	PN315	Manufacturer standard	Handle	X-bore	NBR	NBR	8.5	14613235
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.4	14613242
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	1.6	14613244
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	X-bore	FPM (FKM)	FPM (FKM)	1.6	14613245
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	1.6	14613246
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	X-bore	NBR	NBR	1.6	14613247
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	1.6	14613251
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	X-bore	NBR	NBR	1.6	14613252
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	X-bore	FPM (FKM)	FPM (FKM)	2.6	14613262
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.6	14613263

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.