


GOETZE Spring-loaded safety valve Type 12240 stainless steel high-lifting internal/external thread



Characteristics

Type: 12240

Model: Spring-loaded

Construction type: Angle Pattern

Housing material inlet side: Stainless steel

Material quality inlet side: 1.4408

Housing material outlet side: Stainless steel

Material quality outlet side: 1.4408

Connection inlet side: External thread [BSPP]

Standard connection inlet side: ISO 228-1

Connection outlet side: Internal thread [BSPP]

Standard connection outlet side: ISO 228-1

Blow-off characteristic: High-lifting

Gastight valve: Yes

Spring cap, closed: Yes

Material spring bonnet: 1.4404

Material disc: 1.4404

Seat material: 1.4404

Spring material: 1.4310

Spindle material: 1.4404

Medium temperature: -200 / 200 °C

Application

- Liquefied gases such as LNG, CO₂, LAR. Securing of piping systems and tanks for transport and storage.

Technical Information

- Oil and grease-free as standard for applications with oxygen. Temperature range from -200°C to 200°C.

Options

- Combination with changeover valve type 12270. Version with NPT threaded connection. Complete version with female thread.

DN Inlet [G"]	DN Outlet [Go"]	do [mm]	Ao [mm²]	Setpressure [bar]	L [mm]	h mm	h1 mm	H mm	H1 mm	Weight [kg]
1/4	3/8	6	28	0.2 - 70	21	22	12	60	64	0,2
3/8	3/8	6	28	0.2 - 70	21	22	12	60	64	0,2
3/8	1/2	7,5	44	0.2 - 70	26	27	12	70	73	0,4
1/2	1/2	7,5	44	0.2 - 70	26	27	14	70	73	0,4
1/2	3/4	10,5	86	0.2 - 70	31	31	14	98	103	0,7
3/4	3/4	10,5	86	0.2 - 70	31	31	16	98	103	0,7
3/4	1	13	133	0.2 - 70	38	39	16	134	133	1,3
1	1	13	133	0.2 - 70	38	39	18	134	133	1,3

Press. range	Temperature range
0,2 - 70 barg	-200 °C/ +200° C

Nominal inner diameter inlet side	Nominal inner diameter outlet side	Adjustment range bar	Valve lifter	Sealing	Article
1/4" [8]	3/8" [10]	0.2 / 70	No	PTFE	12987742
3/8" [10]	1/2" [15]	0.2 / 70	No	PTFE	12987744
3/8" [10]	3/8" [10]	0.2 / 70	No	PTFE	12987743
1/2" [15]	1/2" [15]	0.2 / 70	No	PTFE	12987745
1/2" [15]	3/4" [20]	0.2 / 70	No	PTFE	12987746
3/4" [20]	1" [25]	0.2 / 70	No	PTFE	12987748
3/4" [20]	3/4" [20]	0.2 / 70	No	PTFE	12987747
1" [25]	1" [25]	0.2 / 70	No	PTFE	12987749

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.