



LOWARA Submersible pump Series: DOMO roestvaststaal 3 fasen

Characteristics

Series: DOMO

Frequency: 50Hz

Connection: Internal thread (BSPP)

Material pump casing: Stainless steel

Material quality: 1.4301

Pump casing material: Stainless steel SS 304 [1.4301]

Level of protection (IP value): IPX8

Insulation class acc. to IEC: F

Maximum flow rate l/min	Nominal volume flow rate m³/h	Max. immersion depth m	With float	Supply voltage	Length connecting cord m	Rotational speed rpm	Connection size	Article
15500	15.5	5	No	3 x 400V AC	10	2850	1.1/2" [40]	13548884
19000	19	5	No	3 x 400V AC	10	2850	1.1/2" [40]	13548883
24000	24	5	No	3 x 400V AC	10	2850	2" [50]	13548886
30000	30	5	No	3 x 400V AC	10	2850	2" [50]	13548885
33000	33	5	No	3 x 400V AC	10	2850	2" [50]	13548889
36000	36	5	No	3 x 400V AC	10	2850	2" [50]	13548887
40000	40	5	No	3 x 400V AC	10	2850	2" [50]	13548888

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.