



LOWARA Submersible pump Series: DL gietijzer/ roestvaststaal 3 fasen

Characteristics

Series: DL

Frequency: 50Hz

Connection: Internal thread (BSPP)

Material pump casing: Cast iron

Material quality: EN-JL1030

Pump casing material: Stainless steel SS 304 [1.4301]

Level of protection (IP value): IPX8

Insulation class acc. to IEC: F

Maximum flow rate l/min	Nominal volume flow rate m³/h	Max. immersion depth m	With float	Supply voltage	Length connecting cord m	Rotational speed rpm	Connection size	Article
21000	21	5	No	3 x 400V AC	10	2850	2" [50]	13550157
21000	21	5	No	3 x 400V AC	10	2850	2" [50]	13550158
27000	27	5	No	3 x 400V AC	10	2850	2" [50]	13550159
27000	27	5	No	3 x 400V AC	10	2850	2" [50]	13550160
30000	30	5	No	3 x 400V AC	10	2850	2" [50]	13550161
30000	30	5	No	3 x 400V AC	10	2850	2" [50]	13550168
30000	30	5	No	3 x 400V AC	10	2850	2" [50]	13550167
30000	30	5	No	3 x 400V AC	10	2850	2" [50]	13550162
36000	36	5	No	3 x 400V AC	10	2850	2" [50]	13550169
36000	36	5	No	3 x 400V AC	10	2850	2" [50]	13550163
42000	42	5	No	3 x 400V AC	10	2850	2" [50]	13550164

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.