

LOWARA Submersible pump Series: DOC roestvaststaal



Characteristics

Series: DOC

Frequency: 50Hz

Connection: Internal thread (BSPP)

Material pump casing: Synthetic material

Material quality: PPE/PS hars/20% GF

Pump casing material: Stainless steel SS 304 [1.4301]

Level of protection (IP value): IPX8

Insulation class acc. to IEC: B

Maximum flow rate l/min	Nominal volume flow rate m³/h	Max. immersion depth m	With float	Type of switch	Supply voltage	Length connecting cord m	Rotational speed rpm	Connection size	Article
8100	8.1	5	No		1 x 230V AC	10	2850	1.1/4" [32]	13455297
8100	8.1	5	Yes	Model magnetic	1 x 230V AC	10	2850	1.1/4" [32]	13455276
10500	10.5	5	No		1 x 230V AC	10	2850	1.1/4" [32]	13455275
10500	10.5	5	No		3 x 400V AC	10	2850	1.1/4" [32]	13455296
10500	10.5	5	Yes	Model magnetic	1 x 230V AC	10	2850	1.1/4" [32]	13455280
13500	13.5	5	Yes	Model magnetic	1 x 230V AC	10	2850	1.1/4" [32]	13455277
									13455282
									14175543
									14175542
									14175544
									14175545
									14175549
									14175541
									14175546
									14175551
									14175550
									14175539
									14175540
									14175547

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.