

Hose shank brass with male thread type 1VH - flat seal



Characteristics

Type of component: Hose tail coupling

Material: Brass

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: NPT

Elbow angle [degr.]: 45 °

Hose tail execution: Serrated

Temperature range [°C]: -20 / 65 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure bar	Maximum operating pressure psi	Article
				13562364
				13526196
				13526195
1/4"	DN06	6	87	10038956
1/8"	DN06	6	87	10038957
1/2"	DN06	6	87	10038955
3/8"	DN06	6	87	10038958
3/8"	DN08	6	87	10038964
1/8"	DN08	6	87	10038963
1/4"	DN08	6	87	10038962
1/2"	DN08	6	87	12183676
1/4"	DN10	6	87	10038930
1/2"	DN10	6	87	10038929
3/8"	DN10	6	87	10038931
1/2"	DN12	6	87	10038933
1/4"	DN12	6	87	10038935
3/4"	DN12	6	87	10038936
3/8"	DN12	6	87	10038937
1/2"	DN16	6	87	10038939
3/4"	DN16	6	87	11304606
1/2"	DN19	6	87	10038942
3/4"	DN19	6	87	10038940
1"	DN19	6	87	10038941
1"	DN25	6	87	10038946
3/4"	DN25	6	87	11092700
1.1/4"	DN32	6	87	10038949
2"	DN38	6	87	10070455
1.1/2"	DN38	6	87	10038951
2"	DN50	6	87	10038953
1.1/2"	DN50	6	87	11304609
2.1/2"	DN63	6	87	10038960
3"	DN63	6	87	11075341
3"	DN75	6	87	10038961
4"	DN100	6	87	11171144
3/4"	DN25	6	87	12135865
1/2"	DN12	6	87	10038934
1/2"	DN19	6	87	10038943

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.