



WEG 3 Phase motor W22 Cast iron B14T (2P)

Characteristics

Series: W22

Type: B14T

Speed: 3000 rpm

Mounting: B14T

Number of poles: 2

Full load speed: 2720 rpm

Full load torque: 0.411 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE2	0.12	230/400	63	11	90	12318223
IE2	0.18	230/400	63	11	90	12318226
IE2	0.25	230/400	63	11	90	12318229
IE2	0.37	230/400	63	11	90	13025074
IE2	0.37	230/400	71	14	105	12318232
IE2	0.55	230/400	71	14	105	12318236
IE3	0.12	230/400	63	11	90	12687003
IE3	0.12	230/400	63	11	90	13279423
IE3	0.18	230/400	63	11	90	12687008
IE3	0.18	230/400	63	11	90	13279432
IE3	0.25	230/400	63	11	90	12687014
IE3	0.25	230/400	63	11	90	13279440
IE3	0.37	230/400	71	14	105	12687020
IE3	0.37	230/400	71	14	105	13279448
IE3	0.37	230/400	71	14	105	12695009
IE3	0.55	230/400	71	14	105	12687025
IE3	0.55	230/400	71	14	105	13279456
IE3	0.55	230/400	71	14	105	12695010
IE3	0.75	230/400	80	19	120	12687030
IE3	0.75	230/400	80	19	120	13279464
IE3	1.1	230/400	80	19	120	12687046
IE3	1.1	230/400	80	19	120	13279472
IE3	1.1	230/400	80	19	120	12695026
IE3	1.5	230/400	90S	24	140	12687052
IE3	1.5	230/400	90S	24	140	13279480
IE3	1.5	230/400	90S	24	140	12695035
IE3	2.2	230/400	90L	24	140	12687057
IE3	2.2	230/400	90L	24	140	13279488
IE3	2.2	400/690	90L	24	140	12695046
IE3	2.2	400/690	90L	24	140	13190805
IE3	3	230/400	100L	28	160	12687063
IE3	3	230/400	100L	28	160	13279502
IE3	3	400/690	100L	28	160	12695052
IE3	3	400/690	100L	28	160	13190814
IE3	4	230/400	112M	28	160	13402675
IE3	4	230/400	112M	28	160	13402676
IE3	4	400/690	112M	28	160	12687068

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE3	4	400/690	112M	28	160	13279510
IE3	4	400/690	112M			14451487
IE3	5.5	230/400	132S	38	200	13402709
IE3	5.5	230/400	132S	38	200	13402710
IE3	5.5	400/690	132S	38	200	12687073
IE3	5.5	400/690	132S	38	200	13279516
IE3	7.5	230/400	132S	38	200	13402741
IE3	7.5	230/400	132S	38	200	13402742
IE3	7.5	400/690	132S	38	200	12687078
IE3	7.5	400/690	132S	38	200	13279522
IE3	9.2	230/400	132M	38	200	13402768
IE3	9.2	230/400	132M	38	200	13402769
IE3	9.2	400/690	132M	38	200	12687083
IE3	9.2	400/690	132M	38	200	13279526
IE3	11	400/690	132M	38	200	13025207
IE4	0.25	230/400	63	11	90	13310892
IE4	0.25	230/400	63	11	90	13308685
IE4	0.37	230/400	71	14	105	13310897
IE4	0.37	230/400	71	14	105	13308690
IE4	0.55	230/400	80	19	120	13310902
IE4	0.55	230/400	80	19	120	13308695
IE4	0.75	230/400	80	19	120	13310907
IE4	0.75	230/400	80	19	120	13308700
IE4	1.1	230/400	90S	24	140	13310913
IE4	1.1	230/400	90S	24	140	13308705
IE4	1.5	230/400	90L	24	140	13310918
IE4	1.5	230/400	90L	24	140	13308710
IE4	2.2	230/400	100L	28	160	13310923
IE4	2.2	230/400	100L	28	160	13308715
IE4	2.2	400/690	100L	28	160	13403632
IE4	2.2	400/690	100L	28	160	13403633
IE4	3	230/400	L100L	28	160	13310928
IE4	3	230/400	L100L	28	160	13308720
IE4	3	400/690	L100L	28	160	13310933
IE4	3	400/690	L100L	28	160	13308725
IE4	4	230/400	L112M			14156094
IE4	4	230/400	L112M			14156089
IE4	4	400/690	L112M	28	160	13310938
IE4	4	400/690	L112M	28	160	13308730
IE4	5.5	400/690	132S	38	200	12616203
IE4	5.5	400/690	132S	38	200	13194254
IE4	7.5	400/690	132S	38	200	12616208
IE4	7.5	400/690	132S	38	200	13194270
IE4	9.2	400/690	L132M/L	38	200	12616213
IE4	9.2	400/690	L132M/L	38	200	13194280

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.