



WEG 3 Phase motor W22 Cast iron B3R (2P)

Characteristics

Series: W22

Type: B3R

Speed: 3000 rpm

Mounting: B3R

Number of poles: 2

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE3	0.12	230/400	63		12763807
IE3	0.18	230/400	63		12763813
IE3	0.25	230/400	63		12763819
IE3	0.37	230/400	71		12763824
IE3	0.55	230/400	71		12763829
IE3	0.75	230/400	80		12763833
IE3	1.1	230/400	80		12763838
IE3	1.5	230/400	90S		12763843
IE3	2.2	230/400	90L		12763848
IE3	3	230/400	100L		12763854
IE3	4	230/400	112M		12763859
IE3	5.5	230/400	132S		12763866
IE3	5.5	400/690	132S		12763895
IE3	7.5	400/690	132S		13608967
IE3	7.5	230/400	132S		12763868
IE3	7.5	400/690	132S		12763902
IE3	9.2	400/690	132M		12763908
IE3	11	230/400	160M		12763870
IE3	11	400/690	160M		12682904
IE3	15	230/400	160M		12763872
IE3	15	400/690	160M	42	12692058
IE3	18.5	230/400	160L		12763874
IE3	18.5	400/690	160L		12763918
IE3	22	230/400	180M		12763876
IE3	22	400/690	180M	48	12695094
IE3	30	230/400	200L		12763878
IE3	30	400/690	200L	55	12695102
IE3	37	230/400	200L		12763880
IE3	37	400/690	200L	55	12695103
IE3	37	500	200L		13662391
IE3	37	500	200L		13025436
IE3	45	230/400	225S/M		12763882
IE3	45	400/690	225S/M	55	12695110
IE3	55	230/400	250S/M		12763884
IE3	55	400/690	250S/M	60	12695116
IE3	75	400/690	280S/M	65	12695122
IE3	220	400/690	315L		12763949
IE3	250	400/690	315L		12763951
IE3	260	400/690	315L		12763954

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE3	280	400/690	315L		12763956
IE3	315	400/690	355M/L		12763959
IE3	355	400/690	355M/L		12763960
IE4	22	400/690	180M		13672817
IE4	37	230/400	200L		13597129

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.