



KEMPER Backflow preventer Series: 145 2G Type: 2425KB Bronze External thread (BSPP) PN10



Characteristics

Series: 145 2G
Type: 2425KB
Norm: EN (DIN)
Construction type: Free-flow
Housing material: Bronze
Material quality: CC491K
Connection: External thread (BSPP)
Protection class: EA

Application

- Recommended in: Utilities

Nominal inner diameter	Pressure rating	Face to Face length mm	Sealing	Maximum medium temperature (continuous) °C	KIWA	DVGW	Article
1.1/2" [32mm]	PN10	131	EPDM	65	Yes		13427373
1.1/4" [25mm]	PN10	112	EPDM	65	Yes		13427302
1" [20mm]	PN10	97	EPDM	65	Yes		13283029
1.3/4" [40mm]	PN10	148	EPDM	65	Yes		13427374
2.3/8" [50mm]	PN10	174	EPDM	65		Yes	12568671
3/4" [15mm]	PN10	82	EPDM	65	Yes		13190320

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.