


Float valve Type: 730 Float material: Stainless steel External thread (BSPP)




Characteristics

- Type: 730
- Norm: EN (DIN)
- Material quality: 1.4301
- Connection: External thread (BSPP)
- Connection 2: Internal thread (BSPP)
- Pressure rating: PN4
- Face to Face norm: Manufacturer standard
- With float: Yes
- Sealing: PTFE
- Float material: Stainless steel

Characteristics (2)

- Material floating rod: 1.4301
- Minimum medium temperature (continuous): -10 °C
- Maximum medium temperature (continuous): 185 °C
- Maximum pressure difference at 20 °C: 4 bar



Thread connection	L	L1	Weight	Float Ø
["]	[mm]	mm	[kg]	[mm]
3/8	405	445	1,4	120
1/2	430	506	1,6	150
3/4	440	495	2,1	220
1	532	597	3,3	240
1,25	520	597	4,2	240
1,5	538	617	5,4	260
2	575	669	8	300

Max. oper. pressure	Temp.
4 Bar.	185°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Housing material	Nominal inner diameter	Float diameter	Float rod length	Article
		mm	mm	
Stainless steel	3/8" [10]	120	405	11811649
Stainless steel	1/2" [15]	160	430	11811646
Stainless steel	3/4" [20]	220	440	11811648
Stainless steel	1" [25]	240	532	11811643
Stainless steel	1.1/4" [32]	240	520	11811653
Stainless steel	1.1/2" [40]	260	538	11811651
Stainless steel	2" [50]	320	575	11811644