


KEMPER Regulating valve Series: 141 0G Type: 2419K Dynamic Bronze KIWA External thread (BSPP)

bronze regulating- or commisioning valve with threaded connection in PN25.

Area of application

- Heating and cooling systems.
- Industrial applications.
- Installation technique.



Details

- Adjustable Kv values.
- With measuring nipples.
- Oventrop Hydrocontrol VTR.
- Pressure difference and capacity can be measured by a measurement computer.
- Only fig. 2612 has a fill/drain connection.

Characteristics

Series: 141 0G Type: 2419K

Housing material: Bronze Material quality: CuSn5Zn5Pb2 Connection: External thread (BSPP) Type of control gear: Dynamic

Thermostatic: Yes **Application:** Tap water With measuring nipples: Yes

Maximum medium temperature (continuous): 90 °C

KIWA: Yes

With position indicator: Yes

Application

E-mail: valves@eriks.be

• Recommended in: Utilities

Nominal inner diameter	Pressure rating	Adjustment range	Control range	Kvs value	Kv value	Article
		°C	I/h	m³/h	m³/h	
DN25	PN16	50 / 65	410 / 2480	2.48	0.41 / 2.48	11815397

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



Page 1/1

PR2239147987286147_EN_17.05.2024