



ASAHI Ball valve Series: 21 Type: 3731EE PVDF Electric operated Plastic welded sleeve PN10/16

This is a dual-use or controlled item. When exporting this item outside the EU an export license is required from the regulatory authorities.

Characteristics

Series: 21

Type: 3731EE

Construction type: 2-way

Housing construction: 3-part

Housing material: PVDF

Connection: Plastic welded sleeve

Actuator: Electric operated

Seat material: PTFE

Spindle material: PVDF

Primary spindle seal material: FKM-F

Secondary spindle seal material: FKM-F

Body seal: FKM-F

Actuator material: Aluminium

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

Application

- Recommended in: Chemical

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Supply voltage	Bore	Material ball	Kv value m³/h	Article
DN15	20	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	12	13577467
DN15	20	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	12	13577656
DN20	25	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	24.9	13577468
DN20	25	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	24.9	13577657
DN25	32	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	40.3	13577469
DN25	32	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	40.3	13577658
DN32	40	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	62.4	13577470
DN32	40	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	62.4	13577659
DN40	50	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	125.7	13577471
DN40	50	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	125.7	13577660
DN50	63	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	156.9	13577661
DN50	63	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	156.9	13577472
DN65	75	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	320	13577473
DN65	75	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	320	13577662
DN80	90	PN16	Manufacturer standard	ELA60	ECON	24V DC	Full bore	PVDF	430	13577474
DN80	90	PN16	Manufacturer standard	ELA60	ECON	230V AC	Full bore	PVDF	430	13577663
DN100	110	PN10	Manufacturer standard	ELA80	ECON	230V AC	Full bore	PVDF	720	13577664
DN100	110	PN10	Manufacturer standard	ELA80	ECON	24V DC	Full bore	PVDF	720	13577475

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.