



PRESSOL Diesel pump set 12V/24V-35 l/min

Electric diesel pump MOBIFlxx, 35 l/min

- **Self-priming electric pump**

Electric pump - rotary vane pump

PRESSOL lifting protection according to WHG § 19 - constantly effective

Integrated bypass, set to 1.6 bar

Power switch and 3 m electrical cable with battery clamps

- **With 4 m dispenser hose G 1" a**

- Suitable for heating oil and diesel

With automatic dispenser valve with construction type permit

Material: pump casing ALU, pmp GG and PAI

- **Technical data**

Type of protection: IP 54

Fuse: 25A

Activation duration: continuous running 100%

Media temperature: -25 °C to +40 °C

Connection suction/pressure side: G 1"

Pressure head: 1.6 bar

Suction height: max 4 m

- **Extraction performance (measured with diesel at room temperature)**

At free outflow: 35 l/min

With 4 m hose / automatic dispenser valve: 32 l/min

With additional mechanic metre: 30 l/min

Description	Article
Diesel pump set MOBIFlxxE 24V 35l/min	11598467
Diesel pump set MOBIFlxxE, 12V, 35l/min	11598466

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.