



ASECOS Fire protection cabinet with 1 wing door, 1947x564x620 mm



Safety cabinet Q30, RAL 1004

- **Sturdy design in cabinet widths 564, 864 and 1164 mm**

Body:

fire resistant, melamine resin coated special plates in the colour anthracite grey (similar RAL 7016)

Doors:

Made of steel sheeting with structure - powder-coated and optional with large glass window made of fire protection glass EI 30 according to DIN EN 13501-2. Components relating to safety are located outside of the cabinet interior

- **Easy to operate**

Smooth-operating doors, adjustable in any opening position
In the event of fire open doors close independently if open
Door lockable with profile half cylinder
With integrated ventilation and exhaust system for connection NW 75mm) to technical exhaust

- **Interior furnishing**

Standard with 3 height-adjustable shelves (raster 32 mm)
Load capacity 75 kg (evenly spread), floor catchment pan according to StawaR with perforated steel insert as first storage level

- **Easy transport**

Integrated transport base for easy internal transport
Base panel available upon enquiry

- **Fire resistance 30 minutes**

Type 30 safety cabinet for storage of flammable liquids in work rooms according to DIN EN 14470-1 and TRGS 510.
GS certified, CE-conform

Door RAL 1004

Illustration shows variation in RAL 7035 light grey

Width mm	Depth mm	Height mm	Article
564	620	1947	12974969
564	620	1947	12974970
564	620	1947	12974968