

ASECOS Fire protection cabinet with 1 wing door, 1947x864x620 mm



Safety cabinet Q30, RAL 1004

Sturdy design in cabinet widths 564, 864 and 1164 mm

Body:

fire resistant, melamine resin coated special plates in the colour anthracite grey (similar RAL 7016)

Doors:

Made of steel sheeting with structure - powder-coated and optional with large glass window made of fire protection glass El 30 according to DIN EN 13501-2. Components relating to safety are located outside of the cabinet interior

•

Easy to operate

Smooth-operating doors, adjustable in any opening position In the event of fire open doors close independently if open Door lockable with profile half cylinder With integrated ventilation and exhaust system for connection NW 75mm) to technical exhaust

•

Interior furnishing

Standard with 3 height-adjustable shelves (raster 32 mm) Load capacity 75 kg (evenly spread), floor catchment pan according to StawaR with perforated steel insert as first storage level

Easy transport

Integrated transport base for easy internal transport Base panel available upon enquiry

Fire resistance30 minutes

Type 30 safety cabinet for storage of flammable liquids in work rooms according to DIN EN 14470-1 and TRGS 510. GS certified, CE-conform

Door RAL 1004

Illustration shows variation in RAL 7035 light grey

| Width | Depth | Height | Article |
|-------|-------|--------|----------|
| mm | mm | mm | |
| 864 | 620 | 1947 | 12974963 |
| 864 | 620 | 1947 | 12974961 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice.

Page 1/1

ERIKS shall never be liable for damage resulting from the use of the information provided.

