



ASCO Filter reduce fig. 31228 series 652 aluminium internal thread

Characteristics

Series: 652

Type: 31228

Function: Filter-Regulator

Bowl Material: Polycarbonate

Lockable: No

Operating temperature: -20 / 50 °C

Max. outlet pressure [bar]: 10 bar

Weight: 550 g

Material seal: NBR

Filter element material: Polyethylene

Housing material: Aluminium

Port thread type	Port Size	Outlet pressure	Filtration level	With pressure gauge	Drain type	Self-venting	Maximum operating pressure	Max. inlet pressure	Flow Rate (6.3 bar - delta p = 1 bar)	Article
	in	bar	µm					bar	NI/min	
BSPP [G]	1/4	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	4120	12989187
BSPP [G]	1/4	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	4120	12989188
BSPP [G]	1/4	0.5 - 10 bar	5	Yes	Semi automatic	Yes	16	16	3800	12989186
BSPP [G]	3/8	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	5420	12989191
BSPP [G]	3/8	0.5 - 10 bar	5	Yes	Semi automatic	Yes	16	16	4450	12989189
BSPP [G]	3/8	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	5420	12989190
BSPP [G]	1/2	0.5 - 10 bar	5	Yes	Semi automatic	Yes	16	16	4490	12989184
BSPP [G]	1/2	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	5500	12988445
BSPP [G]	1/2	0.5 - 10 bar	25	Yes	Semi automatic	Yes	16	16	5500	12989185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.