



FENNER V-pulley for taper bush section SPA - 4 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: A/SPA/QXPA

Number of grooves: 4

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
13.5	38	13.5
	32	33
	45	20
	45	
	51	14
7	51	7
10	51	10
8	51	8
	65	
12	89	12

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
90	1610	3	Cast iron	12.7	13.5	38	13.5	13924338
95	1610	3	Cast iron	12.7	13.5	38	13.5	11421851
106	2012		Cast iron	12.7				11421865
118	2012	2	Cast iron	12.7		32	33	11421876
125	2012	2	Cast iron	12.7		32	33	11421882
132	2517	2	Cast iron	12.7		45	20	11421888
140	2517	2	Cast iron	12.7		45	20	11421894
150	2517		Cast iron	12.7				11421900
160	2517		Cast iron	12.7				11421907
170	2517	2	Cast iron	12.7		45		11421913
180	2517		Cast iron	12.7				11421919
200	3020	2	Cast iron	12.7		51	14	11421932
224	3020		Cast iron	12.7				11421945
236	3020	7	Cast iron	12.7	7	51	7	13924552
250	3020	7	Cast iron	12.7	10	51	10	11421957
280	3020		Cast iron	12.7				11421965
300	3020	7	Cast iron	12.7	7	51	7	11421971
315	3020	7	Cast iron	12.7	8	51	8	11421978

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
355	3020	5	Cast iron	12.7	7	51	7	11421984
400	3020		Cast iron	12.7				11421989
450	3020	5	Cast iron	12.7	7	51	7	11421995
500	3020	5	Cast iron	12.7	7	51	7	11422000
560	3525	5	Cast iron	12.7		65		11459818
630	3525	4	Cast iron	12.7	12	89	12	11422009
900	3525	4	Cast iron	12.7		65		11459836

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.