



FENNER V-pulley for taper bush section SPA - 5 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: A/SPA/QXPA

Number of grooves: 5

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
48	32	
	32	48
15	51	15
14.5	51	14.5
8	65	8
7.5	65	7.5
2	76	2

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
100	1610		Cast iron	12.7				11421856
106	2012	6	Cast iron	12.7	48	32		11421866
112	2012	6	Cast iron	12.7	48	32		11421871
118	2012	2	Cast iron	12.7		32	48	11421877
125	2012		Cast iron	12.7				11421883
132	2517		Cast iron	12.7				11421889
150	2517		Cast iron	12.7				13924453
160	2517		Cast iron	12.7				11421908
170	3020	3	Cast iron	12.7	15	51	15	11421914
180	3020	3	Cast iron	12.7	14.5	51	14.5	11421920
190	3020	3	Cast iron	12.7	15	51	15	11421926
300	3525	7	Cast iron	12.7	8	65	8	11421972
315	3525		Cast iron	12.7				11421979
355	3525		Cast iron	12.7				11421985
400	3525	4	Cast iron	12.7	7.5	65	7.5	11421990
450	3525	5	Cast iron	12.7	8	65	8	11421996
500	3525		Cast iron	12.7				11422001
560	3525	5	Cast iron	12.7	8	65	8	11459819
630	3525	4	Cast iron	12.7	7.5	65	7.5	11422010
900	4030	5	Cast iron	12.7	2	76	2	11459837

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.