



FENNER V-pulley for taper bush section SPA - 6 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: A/SPA/QXPA

Number of grooves: 6

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
63	32	
25	45	25
22	51	22
15	65	15
9.5	76	9.5
10	76	10

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
106	2012	6	Cast iron	12.7	63	32		11459799
112	2012	6	Cast iron	12.7	63	32		11421872
118	2012	6	Cast iron	12.7	63	32		11421878
132	2517	3	Cast iron	12.7	25	45	25	11421890
140	2517	3	Cast iron	12.7	25	45	25	11421896
150	2517	3	Cast iron	12.7	25	45	25	11421902
160	2517	3	Cast iron	12.7	25	45	25	11421909
170	3020	3	Cast iron	12.7	22	51	22	11421915
180	3020	3	Cast iron	12.7	22	51	22	11421921
200	3020	3	Cast iron	12.7	22	51	22	11421934
250	3020	7	Cast iron	12.7	22	51	22	11421959
280	3525	7	Cast iron	12.7	15	65	15	11421967
315	3525	7	Cast iron	12.7	15	65	15	11421980
355	3525	5	Cast iron	12.7	15	65	15	11459807
400	3525	5	Cast iron	12.7	15	65	15	11421991
630	4030	4	Cast iron	12.7	9.5	76	9.5	11459822
900	4030	5	Cast iron	12.7	10	76	10	11422016

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.