



FENNER V-pulley for taper bush section SPC - 4 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 4

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
23	65	23
11	89	11
4.5	102	4.5

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
200	3020		Cast iron	22				11422229
212	3020		Cast iron	22				11422235
236	3525		Cast iron	22				23836056
250	3525	3	Cast iron	22	23	65	23	11422247
280	3525	3	Cast iron	22	23	65	23	11422258
315	3525	7	Cast iron	22	23	65	23	11422269
335	3525	7	Cast iron	22	23	65	23	11422275
355	3525	7	Cast iron	22	23	65	23	11422279
355	3535		Cast iron	22				13925274
375	3525	7	Cast iron	22	23	65	23	11422285
400	3525	5	Cast iron	22	23	65	23	11422290
425	3525	5	Cast iron	22	23	65	23	11422297
450	3525	5	Cast iron	22	23	65	23	11422302
475	3525	5	Cast iron	22	23	65	23	11422309
500	3525	5	Cast iron	22	23	65	23	11422313
530	3525	5	Cast iron	22	23	65	23	11422317
560	3525	5	Cast iron	22	23	65	23	11459821
710	4535	5	Cast iron	22	11	89	11	11459829
800	5040	4	Cast iron	22	4.5	102	4.5	11422331

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.