



FENNER V-pulley for taper bush section SPC - 5 grooves

Fenner® Taper Lock® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 5

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
35.5	65	35.5
23.5	89	23.5
17	102	17

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
200	3525	3	Cast iron	22	35.5	65	35.5	11422230
212	3525	3	Cast iron	22	35.5	65	35.5	11422236
224	3525	3	Cast iron	22	35.5	65	35.5	11422240
236	3525	3	Cast iron	22	35.5	65	35.5	11422245
250	3525	3	Cast iron	22	35.5	65	35.5	11422248
265	3525	3	Cast iron	22	35.5	65	35.5	11422254
280	3525	3	Cast iron	22	35.5	65	35.5	11422259
300	3525	7	Cast iron	22	35.5	65	35.5	11422266
315	3525	7	Cast iron	22	35.5	65	35.5	11422270
355	3525	7	Cast iron	22	35.5	65	35.5	11422280
400	3525	5	Cast iron	22	35.5	65	35.5	11422291
425	3525	5	Cast iron	22	35.5	65	35.5	11422298
450	3525	5	Cast iron	22	35.5	65	35.5	11422303
500	3525	5	Cast iron	22	35.5	65	35.5	11449808
530	4535		Cast iron	22				13925365
560	4535	5	Cast iron	22	23.5	89	23.5	11422320
630	4535	5	Cast iron	22	23.5	89	23.5	11422325
800	5040	5	Cast iron	22	17	102	17	11422332

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.